

SURETHERM 10X



SPECIFICATIONS

Power Rating	3 kVA
Facility Power	110 - 230 V / 13 A / 50/60 Hz
Temperature Control	Single / Dual
Weight	21 kg / 46.3 lb
Operating Area (WxH)	120 x 145 mm
Dimensions (LxBxH)	450 x 210 x 130 mm
WORKPIECE	
Min. bore diameter	ø 10 mm / ø 0.4 inches
Max. outer diameter	ø 400 mm / ø 15.75 inches
Max. weight	50 kg / 110 lb

SURETHERM 20X



SPECIFICATIONS

Power Rating	3.7 kVA
Facility Power	110 - 230 V / 16 A / 50/60 Hz
Temperature Control	Single / Dual
Weight	40 kg / 88 lb
Operating Area (WxH)	180 x 185 mm
Dimensions (LxBxH)	540 x 275 x 130 mm
WORKPIECE	
Min. bore diameter	ø 15 mm / ø 0.6 inches
Max. outer diameter	ø 500 mm / ø 19.7 inches
Max. weight	100 kg / 220 lb

SURETHERM 30X



SPECIFICATIONS

Power Rating	8 kVA
Facility Power	400 - 575 V / 20 A / 50/60 Hz
Temperature Control	Single / Dual
Weight	85 kg / 187 lb
Operating Area (WxH)	210 x 220 mm
Dimensions (LxBxH)	695 x 330 x 160 mm
WORKPIECE	
Min. bore diameter	ø 30 mm / ø 1.2 inches
Max. outer diameter	ø 600 mm / ø 23.6 inches
Max. weight	200 kg / 440 lb

SPECIFICATIONS

Power Rating	12.8 kVA
Facility Power	400 - 480 - 575 V / 32 A / 50/60 Hz
Temperature Control	Single / Dual
Weight	157 kg / 346 lb
Operating Area (WxH)	300 x 330 mm
Dimensions (LxBxH)	850 x 420 x 950 mm

WORKPIECE

Min. bore diameter	ø 30 mm / ø 1.2 inches
Max. outer diameter	ø 1000 mm / ø 39.4 inches
Max. weight	400 kg / 880 lb



SURETHERM PRO 3X

SPECIFICATIONS

Power Rating	25.2 kVA
Facility Power	400 - 480 - 575 V / 63 A / 50/60 Hz
Temperature Control	Single / Dual
Weight	280 kg / 617 lb
Operating Area (WxH)	430 x 490 mm
Dimensions (LxBxH)	1080 x 500 x 1250 mm

WORKPIECE

Min. bore diameter	ø 45 mm / ø 1.8 inches
Max. outer diameter	ø 1500 mm / ø 59 inches
Max. weight	800 kg / 1764 lb



SURETHERM PRO 6X

SPECIFICATIONS

Power Rating	40 kVA
Facility Power	400 - 480 - 575 V / 100 A / 50/60 Hz
Temperature Control	Hz
Weight	Single / Dual
Operating Area (WxH)	650 kg / 1433 lb
Dimensions (LxBxH)	690 x 700 mm

WORKPIECE

Min. bore diameter	ø 85 mm / ø 3.35 inches
Max. outer diameter	ø 2000 mm / ø 78.75 inches
Max. weight	1600 kg / 3527 lb

